



Large LCD display



625 is digital Humidity & Temperature Meter with Wet Bulb Temperature & Dew Point temperature, which has been designed to combine the functions of Humidity Meter, Temperature Meter, Wet Bulb Temperature and Dew point temperature.

It is an ideal Humidity & Temperature Meter instrument with scores of practical applications for laboratorial, industrial, Engineer and professional use.

615 is Humidity meter plus Air and type K thermocouple thermometer.

- Large, easy-to-read backlit LCD with dual display
- Fast Response Time %RH: 10s (90% at 25°C still air)
- 2% High Accuracy (625)
- Dew Point Temperature (-30°C~100°C/-22°F~199°F) (625)
- Wet Bulb Temperature (0°C~80°C/32°F~176°F) (625)
- Resolution 0.1%RH, 0.1°C/0.1°F
- Max/Min Hold and Data Hold Function (625)
- Micro Processor-based Design (625)
- Dual Display Temperature & Humidity

Features

	615	625
Large dual digital LCD display with backlight	*	*
Response Time%RH:10s (90% at +25°C still air)		*
Sampling Rate 2.5 samples per second	*	*
Dew Point Temperature & Wet Bulb Temperature		*
2% High Accuracy		*
Dual Display Temperature & Humidity	*	*
Type K temperature	*	



High Performance and quality sensor

Specifications

Function	Range	Resolution	Basic Accuracy	615	625
Humidity	0°C~100%RH	0.1%RH	±2%RH		*
			±3.5%RH	*	
Temperature	-30°C~100°C/-30°F~199°F	0.1°C/°F	±0.5°C/0.9°F		*
Type K Temp.	-20°C~1000°C/ -4°F~1832°F	0.1° up to 200°, 1° over 200°	±3%	*	
Dew Point Temp.	-30°C~100°C/-22°F~199°F	0.1°C/°F	±1.0°C/1.8°F		*
Wet Bulb Temp.	0°C~80°C/32°F~176°F	0.1°C/°F	±1.0°C/1.8°F		*

Size(HxWxD): 225mm x 45mm x 34mm

Weight: 200g

Accessories:

Carrying case, type K temperature probe (615) and 9V battery.